

## Optical Traffic Grooming

### Field of the invention

The present invention relates broadly to a method and apparatus for connecting network elements between optical networks supporting different bit rate data streams.

### Background of the invention

In optical networks it is often required to forward traffic from multiple separate users received at a core node of e.g. a metro dense wavelength division multiplexing (DWDM) networks onto another long-haul network using a different bit rate data stream than the metro DWDM network.

In designing a system that facilitates such connectivity it must also be considered that subscribers (i.e. users) will need to communicate to different locations on the long-haul network.

At least preferred embodiments of the present invention seek to provide a method and apparatus for facilitating such connectivity in optical networks.

### Summary of the invention

In accordance with a first aspect of the present invention there is provided a network hub structure for connecting network elements of a first WDM network supporting a first bit rate WDM data stream to other network elements on a second optical network supporting a second bit rate data stream which is substantially a multiple  $n$  of the first bit rate; the hub structure comprising a multiplexing system comprising a plurality of multiplexing units, each multiplexing unit being arranged to multiplex  $n$  first WDM data streams into one second data stream, and a switching unit arranged, in use, to selectively cross connect any  $n$  first WDM data streams originating from one or more of the network elements of the WDM network destined for any same one of said other network elements to one of the multiplexing units for multiplexing into one said second data stream.

In a preferred embodiment, the first bit rate WDM data streams are 1 Gbit/s Gigabit Ethernet data streams, and the second bit rate data streams are 2.488 Gbit/s SONET/SDH (OC48) data streams.

Each multiplexing unit may comprise a 2xGbE/OC48 Packet Over SONET (POS) multiplexer unit.

In another embodiment, each multiplexing unit may comprise a SONET time division multiplexing (TDM) multiplexer unit. Advantageously, the SONET TDM multiplexer units are arranged, in use, to first decode 1.25 Gbit/s 8b/10b encoded GbE streams to produce two 1 Gbit/s streams, and to then multiplex the two 1 Gbit/s streams into SONET Virtual Containers. Alternatively, the SONET TDM multiplexer units may be arranged, in use, to first decode the 1.25 Gbit/s 8b/10b encoded GbE streams to produce two 1 Gbit/s streams, and to then multiplex the two 1 Gbit/s streams into a SONET frame in alternate time slots. In such an embodiment, the SONET TDM multiplexer units are preferably arranged in a manner such that, in use, additional filler bytes are being inserted to match to the capacity of the SONET frame.

The SONET TDM multiplexer units may further be arranged in a manner such that, in use, the decoded GbE streams are being re-encoded utilising a 5b/6b line code to produce 1.2 Gbit/s streams, before employing the multiplexing into the 2.488 Gbit/s OC 48 data streams.

Each multiplexing unit is preferably arranged to de-multiplex an incoming second data stream from the second network into  $n$  outgoing first WDM data streams destined for network elements on the first WDM network, and the switching unit is arranged to cross connect said outgoing first WDM data streams to a WDM unit if the network hub structure for multiplexing the outgoing first WDM data streams onto the first WDM network.

Each multiplexing unit advantageously comprises a tagging unit for tagging each first WDM data stream, and for allocating a wavelength to each outgoing first WDM data stream based on tags on the incoming second data streams.

Preferably, each multiplexing unit is incorporated in a Line Interface Card interfacing to a core hub on the second network.

The network hub structure may further comprise a plurality of Trunk Interface Cards disposed before the switching unit for interfacing to the first WDM network.

The network hub structure advantageously further comprises a redundant switching unit for fault protection, the redundant switching unit being arranged, in case of a fault in the primary switching unit, to selectively cross connect the any  $n$  first WDM data streams originating from one or more of the network elements of the WDM network destined for the any

same one of said other network elements to the one of the multiplexing units for multiplexing into one said second data stream.

The second network may be a second WDM network.

In accordance with a second aspect of the present invention there is provided a method for connecting network elements of a first WDM network supporting a first bit rate WDM data stream to other network elements on a second optical network supporting a second bit rate data stream which is substantially a multiple  $n$  of the first bit rate; the method comprising the steps of selectively multiplexing any  $n$  first WDM data streams originating from one or more of the network elements of the WDM network destined for any same one of said other network elements into one said second data stream.

In a preferred embodiment, the first bit rate WDM data streams are 1 Gbit/s Gigabit Ethernet data streams, and the second bit rate data streams are 2.488 Gbit/s SONET/SDH (OC48) data streams.

The method preferably further comprises the step of de-multiplexing an incoming second data stream from the second network into  $n$  outgoing first WDM data streams destined for one or more network elements on the first WDM network and multiplexing the outgoing first WDM data streams onto the first WDM network.

The method advantageously comprises the step of tagging each first WDM data stream, and allocating a wavelength to each outgoing first WDM data stream based on tags on the incoming second data streams.

### **Brief description of the drawings**

Preferred forms of the present invention will now be described, by way of example only, with reference to the accompanying drawings.

Figure 1 is a schematic drawing illustrating a core hub structure embodying the present invention.

Figure 2 is a schematic drawing illustrating a Gigabit Ethernet Trunk Interface Card embodying the present invention.

Figure 3 is a schematic drawing illustrating an OC48/2xGbE Line Interface Card embodying the present invention.

Figure 4 is a schematic drawing illustrating the main functional components of an OC48/2xGbE Multiplexing Unit.

Figure 5 is a functional block diagram of a core hub structure embodying the present invention.

Figure 6 is a schematic drawing illustrating the connectivity between a metro ring network and a core network facilitated through the core hub structure of Figure 1.

### **Detailed description of the embodiments**

In the preferred embodiments described, a core hub structure is provided which facilitates connecting network elements of a metro network supporting a first bit rate data stream to other network elements on a core network supporting a second bit rate data stream which is substantially a multiple  $n$  of the first bit rate data stream, which makes it possible for different customers on the metro network to communicate to different locations on the long-haul network.

In the core hub structure 100 shown in Figure 1, 32 GbE Trunk Interface Cards (TICs) e.g. 102 are fitted to transmit and receive 32 full-duplex GbE streams, e.g. 104, out of a DWDM multiplexed Metro backbone fibre ring 106. The 32 GbE streams originate from network elements (not shown) on the Metro backbone fibre ring network 16. The functions of each GbE TIC e.g. 102 are to receive and regenerate the incoming GbE DWDM channel of the full duplex stream e.g. 104, to transmit the outgoing GbE DWDM channel of the full-duplex stream e.g. 104, and to connect the full duplex GbE stream to one of two redundant cross-connect switches 108, 110, via one of two intra-office optical interconnects 112, 114. Note that in the structure 100 shown in Figure 1, Switch A 108 is the primary switch, that is used in normal operation, whereas Switch B 110 is a secondary switch that is provided for protection, and which will be used in case of a failure in Switch A 108.

Figure 2 shows the structure 200 of a GbE TIC e.g. 102 in the form of a functional block diagram. A full duplex DWDM GbE stream 202 is connected from the DWDM network 106 (Figure 1) to a DWDM transceiver 204. The transceiver 204 may comprise a broadband receiver such as e.g. a semiconductor PIN detector, to receive the incoming GbE channel. The

Returning now to Figure 1, and considering first the connections via the primary cross-connect switch 108. The primary cross-connect switch 108 may be either of an all optical (OOO) type, in which case the switching is performed using an optical switch matrix, or it may be of an optical-electronic-optical (OEO) type, in which case the optical signals e.g. 112, are converted back into electrical form via an optical transceiver, and then switched using an electronic switch matrix, before being converted back into optical form via a second optical transceiver. In the embodiment 100 shown, the cross-connect switch 108 comprises at least a 64x64 switch matrix (i.e. having 64 input ports and 64 output ports).

The cross-connect switch 108 has the capability to connect any two GbE streams coming from two GbE TIC's e.g. 102, 120 and entering the switch 108 at e.g. ports 122 and 124 to any of 32 output ports e.g. 126, 128 wherein each pair of optical connections e.g. 118, 130 is connected to one of 16 OC48/2xGbE Line Interface Cards (LICs) e.g. 132.

The two GbE streams selected by the switches 310, 312 are connected to an OC48/2xGbE multiplexing unit 314 that combines them into a single full-duplex 2.488 Gbit/s OC48 stream 316. The OC48 stream 316 is connected to a further optical transceiver 318, which is connected via an optical link 320 to the core network terminal equipment. The optical link 320 may comprise e.g. a SONET/SDH OC48 short haul intra-office connection operating at a nominal wavelength of 1310 nm over single-mode fibre. Accordingly, the optical transceiver 318 may comprise a suitable 1310 nm laser transmitter and PIN photo-receiver, as specified in the relevant SONET/SDH standards documents.

The dual Gigabit Ethernet controller 406 includes a serialiser/deserialiser unit 408 for converting the two GbE streams 402, 404 between serial and parallel formats. The dual Gigabit Ethernet controller 406 further includes a dual GbE Medium Access Control (MAC) unit for

The 2.488 Gbit/s SONET/SDH user network interface device 426 includes a PL3 Slave unit 428 for transmitting and receiving packets over the standard PL3 channel 424. The user network interface device 426 further includes a SONET/SDH processing unit that provides SONET/SDH framing and path overhead functionality. The user network interface device 426 further includes a serialiser/deserialiser unit 432 for converting the 2.488 Gbit/s SONET/SDH stream 434 between parallel and serial formats.

Returning now to Figure 1, each DWDM Ring Interface 116, 138 provides for the multiplexing of 16 DWDM channels onto the metro DWDM network 106. Figure 5 shows an alternative representation 500 of the functional blocks that comprise the core hub 100. The DWDM Ring Interface 502 includes a DWDM Multiplexer/Demultiplexer (MUX/DEMUX) Unit 504, a Coarse WDM (CWDM) Unit 506, a Management Channel MUX/DEMUX 508 and a Hub Bypass Switch 510. The Hub Bypass Switch 510 provides the physical connection to the metro ring network, and enables the hub to be physically disconnected from the network. The Management MUX/DEMUX Unit 508 is used to add and drop a single wavelength (at around 1510 nm in the exemplary embodiment) that is used as a network management channel. The data on the network management channel is processed by a Management Processing Unit 514,





hub 606 to form a first OC48 channel 618. Additionally, a third GbE channel 610 from the first metro hub 604 is combined at the core hub 616 with a fourth GbE channel 614 from the second metro hub 606 to form a second OC48 channel 620. The OC48 channels 618, 620 are transmitted via short-haul intra-office links to the first core network terminal unit 622, from which they are transmitted via the core network 602 to second and third core network terminal units 624, 626 respectively.

Network elements 624 and/or 626 located on the core network 602 may in turn be connected to core hubs interfacing to another metro network, and the GbE data streams e.g. 608, 610, 612, 614 may be destined to different metro network elements on that other metro network. The OC48 data streams e.g. 618, 620 may thus be received at the network elements 624 and/or 626 and transmitted as indicated by arrows 628, 630 to corresponding metro network core hubs (not shown), where they are demultiplexed into the corresponding GbE data streams 608, 610, 612, 614, which are then connected through to their respective destination metro network elements on the other metro networks.

Returning again to Figure 1, it will be appreciated that additionally, any individual full-duplex GbE channel e.g. 104 received via the metro DWDM network 106 may be switched from the corresponding GbE TIC to any other GbE TIC, e.g. 120, from which it may be transmitted back into the metro DWDM network 106 via a different DWDM channel e.g. 134.

It will further be appreciated that the provision of a second redundant switch 110, along with the switching capability provided by each TIC and LIC enables the core hub 100 to continue operating even if one of the cross-connect switches fails. Thus the core hub 100 has no single point of failure that may cause all channels to be disconnected.

Accordingly, the exemplary embodiment shown in Figure 1 is able to provide a highly fault-tolerant grooming function for GbE channels that enables each individual channel to be independently switched between any source and any destination either on the metro DWDM network or across the core transport network, while making optimum use of the 2.488 Gbit/s transmission capacity provided by the SONET/SDH OC48 channels provided by the core network.

It will be appreciated by a person skilled in the art that numerous variations and/or modifications may be made to the present invention as shown in the specific embodiments

without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects to be illustrative and not restrictive.

For example it will be appreciated that the grooming of 32 GbE streams into 16 OC48 streams is an exemplary configuration only.

Furthermore, the present invention is not limited to GbE into OC48 grooming, but may applied for other data streams, including 4xOC12 into OC48 or 16xOC3 into OC48.

11/11/2009 10:00:00 AM